

# CST™ 282

Issued Sept. 2025 • Index No. DC/29.6

Stick/TIG Welding  
Power Source



## Quick Specs



### Industrial Applications

Power plant construction  
Petrochemical construction  
Maintenance and repair  
Shipbuilding

### Processes

Stick (SMAW)  
TIG (GTAW) Lift-Arc™

**Input Power** 208–575 V, 3- or 1-phase power

**Amperage Range** Stick: 30–280 A, TIG: 5–280 A

**Max. Open-Circuit Voltage** 103 VDC

**Net Weight** 34.6 lb. (15.7 kg)

**Superior stick arc performance** with settings specifically designed for XX10 and XX18 electrodes and a stiff and soft setting for each. Whether welding pipe or in the flat there is a setting for each application. The last amperage used for each of the processes is retained, so when you return from a different process the last setting is loaded and you are ready to go.

**Adaptive Hot Start™** for stick arc starts automatically increases the output amperage at the start of a weld. Prevents the electrode from sticking.

**Lift-Arc™** start provides TIG arc starting without the use of high frequency.

**Digital meter** for more precise control when presetting or monitoring welding amperage.

**Portable** in the shop or at the jobsite — at 34.6 pounds the CST 282 is easily moved from location to location.

**14-pin receptacle** on front of the machine provides the flexibility to use remote controls to adjust the amperage and turn the output on and off.

**Fan-On-Demand™** cooling system operates only when needed, providing power efficiency and noise reduction.

**Six-foot power cable included.**

**Rack mountable** for protection, storage and transportation of multiple power sources while using a single primary power cable.



Welds Stick/TIG



Portable



Simple, Accurate Interface



Flexible



CST 282 with Tweco-style receptacles shown.



For portability and reliability, Auto-Line allows for any input voltage hookup (208–575 V, single- or three-phase) with no manual linking, providing convenience in any job setting. Ideal solution for dirty or unreliable input power.

**Universal connector system** allows the machine to be quickly configured to either Tweco®, Dinse-, or Cam-Lok-style receptacles. Extra receptacles and wrench shown are sold separately as Universal Connector Kits (see page 4).



Power source is warranted for three years, parts and labor.  
Original main power rectified parts are warranted for five years.



**Miller Electric Mfg. LLC**  
An ITW Welding Company  
1635 West Spencer Street  
P.O. Box 1079  
Appleton, WI 54912-1079 USA

**Equipment Sales US and Canada**  
Phone: 866-931-9730  
International Phone: 920-735-4554

**MillerWelds.com**  
f X YouTube Instagram LinkedIn




# Specifications (Subject to change without notice.)



Welding Mode	Input Power	Welding Amperage Range	Rated Output	Amps Input at Rated Load Output, 50/60 Hz					KVA	KW	Max. Open-Circuit Voltage	Dimensions	Net Weight
				208 V	230 V	400 V	460 V	575 V					
Stick (SMAW)	Three-phase	30–280 A	280 A at 31.2 VDC, 35% duty cycle	29.63	26.65	15.71	13.92	12.08	12	10.2	103 VDC	H: 13.5 in. (343 mm) W: 8 in. (203 mm) D: 18.5 in. (470 mm)	34.6 lb. (15.7 kg)
			200 A at 28 VDC, 100% duty cycle	18.86	17.09	10.6	9.37	8.02	8	6.4			
	Single-phase	30–280 A	200 A at 28 VDC, 50% duty cycle*	33.7	30.65	17.61	16.18	14.51	8.3	6.6	103 VDC		
			150 A at 26 VDC, 100% duty cycle*	23.07	20.59	12.97	11.8	11.15	6.4	4.5			
TIG (GTAW)	Three-phase	5–280 A	280 A at 21.2 VDC, 35% duty cycle	20.77	18.85	11.54	10.22	8.95	8.9	7.1	9.5 VDC		
			200 A at 18 VDC, 100% duty cycle	12.89	11.74	7.42	6.55	5.49	5.4	4.3			
	Single-phase	5–280 A	200 A at 18 VDC, 50% duty cycle*	22.12	19.71	12.89	11.06	10.61	6.1	4.4	9.5 VDC		
			150 A at 16 VDC, 100% duty cycle*	14.84	13.38	8.73	8.63	7.72	5.1	2.9			

Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

## Control Panel




1. Output Indicator Light
2. High Temperature Shutdown Light
3. VRD Indicator Light\*
4. Power Switch
5. Electrode Indicator Lights
6. Stick Process Select
7. Amps Display
8. Amperage Adjustment Buttons
9. Arc Control Indicator Lights
10. Arc Control Select
11. Lift-Arc Indicator Light
12. TIG Process Select

\*Voltage Reducing Device (VRD) — see Owner's Manual for more information.

## Performance Data

Duty Cycle Chart



# Genuine Miller® Accessories

## TIG (GTAW) Torches



### Weldcraft™ TIG Torches

The Weldcraft line of air-cooled and water-cooled TIG torches complements the most popular TIG power source line available today.

#### A-150 Valve

**WP-17V-12-2** 12 ft. (3.7 m)

**WP-17V-25-2** 25 ft. (7.6 m)

150-amp air-cooled torch with valve and two-piece cable.

#### A-200 Valve

**WP-26V-12-2** 12 ft. (3.7 m)

**WP-26V-25-2** 25 ft. (7.6 m)

200-amp air-cooled torch with valve and two-piece cable.

*These two-piece-cable TIG torches require the installation of a Tweco®-style connector (191981) or Dinse-style connector (042533) depending on the CST receptacle type.*

## Remote Controls



### RCC-14 Remote Contactor and Current Control 151086

East/west rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord and 14-pin plug.



### RCCS-14 Remote Contactor and Current Control 043688

North/south rotary-motion fingertip control attaches to TIG torch using two hook-and-loop fasteners. Includes 26.5-foot (8 m) cord and 14-pin plug.



### RHC-14 Hand Control 242211020

20 ft. (6 m)

**242211100** 100 ft. (30.5 m)

Miniature hand control for remote current and contactor control. Dimensions: 4 x 4 x 3.25 inches (102 x 102 x 82 mm). Includes cord and 14-pin plug.

3.25 inches (102 x 102 x 82 mm). Includes cord and 14-pin plug.



### RFCS-14 HD Foot Control 194744

Heavy-duty foot pedal current and contactor control with increased stability and durability from larger base and heavier cord. Reconfigurable cord can exit front, back or either side of the pedal for flexibility. Includes 20-foot (6 m) cord and 14-pin plug.



### Wireless Remote Foot Control 301580

For remote current and contactor control. Receiver plugs directly into the 14-pin receptacle of Miller® machine. 90-foot (27.4 m) operating range.



### Wireless Remote Hand Control 301582

For remote current and contactor control. Receiver plugs directly into the 14-pin receptacle of Miller® machine. 300-foot (91.4 m) operating range.

### Extension Cables for 14-Pin Remote Controls

**242208025** 25 ft. (7.6 m)

**242208050** 50 ft. (15.2 m)

## CST™ 282 Rack (See Multioperator Racks literature DC/19.0 for more information.)



CST 8-Pack Rack

CST 4-Pack Rack

- The rack provides a simple means of protecting and transporting multiple welding power sources for construction, power plant turn-arounds and shipbuilding applications.
- One easy connection allows up to eight inverters to be connected with one primary power drop.
- All controls including power switch are located on front of machine for easy access.
- Top cover protects machines from falling debris.
- Lift eye(s) simplify crane or overhead lifting device transport.
- Lift truck fork pockets.
- Common output ground connection (for same polarity use only).
- Racks include casters that can be bolted to the rack base. Two swivel casters and two non-swivel casters. Large 5-inch diameter wheels enable the rack to be moved over grating and driveway gravel.

### CST Rack Specifications

Power Source	Input Power to Rack	Capacity	Dimensions	Net Weight
CST 282	208–575 V, three-phase, 50/60 Hz (fused for 460 V)*	4	H: 50.75 in. (1,289 mm) W: 25.5 in. (648 mm) D: 26.5 in. (673 mm)	330 lb. (150 kg)
		8	H: 59.375 in. (1,508 mm) W: 43 in. (1,092 mm) D: 34.375 in. (873 mm)	550 lb. (250 kg)

\*Fuses included for 460-volt operation. 575-volt operation requires separate fuse (248810). 40 A fuse for 208/230-volt operation is **NOT** available from Miller — check with your local distributor or other source. Empty rack orders require ordering the appropriate fuse kit.

## Ordering Information

Power Source	Stock No.	Description	Qty.	Price
CST™ 282	907770	208–575 V, Tweco®-style receptacles		
	907810	208–575 V, Dinse-style receptacles		
CST™ 282 Racks	951883	4-pack, 208–575 V, fused 460 V, Tweco®-style receptacles		
	907812	8-pack, 208–575 V, fused 460 V, Tweco®-style receptacles See Multioperator Racks literature DC/19.0 for more information		
<b>Accessories</b>				
Empty CST™ Racks	951934	208–575 V, Holds up to four CST 280 models		
	301610	208–575 V, Holds up to eight CST 280 models See Multioperator Racks literature DC/19.0 for more information <i>Note: Order <b>required</b> fuse(s) below for appropriate primary voltage</i>		
CST Rack Fuses (order 12 per 4-pack rack or 24 per 8-pack rack)	220074	20 A, individual fuse for 460 V		
	248810	15 A, individual fuse for 575 V <i>Note: 40 A fuse for 208/230 V operation is <b>NOT</b> available from Miller — check with your local distributor or other source</i>		
<b>Weldcraft™ TIG Torches</b>				
		See page 3		
<b>Remote Controls</b>				
		See page 3		
<b>Cable Connectors and Adapters</b>				
Universal Connector Kits	301611	Includes Tweco-style receptacles, wrench and electrical joint compound		
	301595	Includes Dinse-style receptacles, wrench and electrical joint compound		
	301637	Includes Cam-Lok-style receptacles, wrench and electrical joint compound		
Tweco-Style Connector	191981	#1/0 to #2/0 AWG cable size		
Dinse-Style Connector	042533	#1/0 to #2/0 AWG cable size		

Date:

Total Quoted Price:

Distributed by:

